



**DIMENSIONS**

Proper installation and satisfactory operation of a standard WILDECK lift requires seven dimensions. The required dimensions are listed in the following chart.

- A Vertical Rise .....
- B Carriage Length .....
- C Carriage Width .....
- D Carriage Thickness .....
- E Load Height .....
- F Upper Level Opening (length) .....
- G Upper Level Opening (width) .....

**NOTES**

1. All carriages are 4 1/4" thick.
2. If ramp is not used, a pit can be provided. For a 4 1/4" thick carriage, a 5" pit is required.
3. The load height is not relevant to the overall height of this unit.

CONCEPTUAL DRAWING  
per Quote # \_\_\_\_\_

NO.	DATE	DESCRIPTION	BY
WILDECK, INC. 405 COMMERCE ST. WAUKESHA, WI 53186 (800) 325-6939 (262) 549-4000 WILDECK.COM		<b>WILDECK</b> <sup>®</sup>	
VERTICAL RECIPROCATING CONVEYOR HYDRAULIC CANTILEVER			
MODEL NUMBER: HLC-X		DWG No.	REV
DIMENSIONAL INFORMATION		<b>HYD CANT INFO</b>	<b>0</b>

WILDECK, INC. RESERVES PROPRIETARY RIGHTS TO THIS DRAWING AND DATA SHOWN THEREON. SAID DRAWING AND/OR DATA ARE CONFIDENTIAL AND ARE NOT TO BE USED OR REPRODUCED FOR ANY PURPOSE WITHOUT THE WRITTEN CONSENT OF WILDECK, INC.

**THIS DRAWING IS CONCEPTUAL ONLY**  
Not to be Used for Installation or Construction.